



كونتيننتال الزيوت وزيوت التزييت مروح Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

CONTEX SUPREME OVAL SAE 20W60 API CF-4 SG

Description

CONTEX SUPREME OVAL SAE 20W60 API CF-4 SG is a high-quality multigrade engine oils for heavy duty applications in on-highway service.

CONTEX SUPREME OVAL SAE 20W60 API CF-4 SG are blended with specifically selected high quality mineral and semi-synthetic base stocks together with proven additive technology and viscosity index improver, providing high performance and good durability in service.

Application:

Recommended for use in diesel or mixed fleet (diesel gasoline) engine operations on highway service. It is intended for the lubrication of heavy duty diesel engines, naturally aspirated or turbocharged, working under variable conditions and over wide temperature ranges whose manufacturers recommend API CF-4 performance level oils in various types of service including engines used in heavy-duty trucks, construction, mining and farming equipments.

FEATURES & BENEFITS

- Exhibits easier cold weather starting
- Resists breakdown at high temperatures.
- Resisting deposits caused by soot and acids
- Withstands the stress of heat, wear and corrosion
- Longer drain intervals and smooth running of engines.
- Good compatibility with rubber to Protect rubber seals.
- Increases fuel economy due to ultra-low vaporization loss.
- Specially designed for Engine with EGR and turbochargers □tted.
- Highly efficient in dispersancy and detergency keeps engine clean.
- Reduces Kinetic energy loss out of friction wear by effectively dispersing ash and deposits.

Performance Specification

This product meets or exceeds the following specifications- API CF-4 and lower API



كونتيننتال الزيوت وزيوت التزييت م.م.ح Continental Oils & Lubricants F.Z.E.

Typical Physical Characteristics

Particulars	Method	Values
Density,kg/m ³	ASTM D4052	892.1 at 15° C
Kinematic Viscosity at 100 ° C, mm ² /s	ASTM D445	24.6
Viscosity Index	ASTM D2270	123
TBN mg KOH/g	ASTM D2896	9.5
Sulphated Ash	ASTM D874	1.4
Flash Point	ASTM D92	230
Pour Point		-25