



كونتيننتال الزيوت وزيوت التزييت مروح Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

CONTEX SUPREME VOLT SAE 15W40 API CI-4/SL

Description

CONTEX SUPREME VOLT SAE 15W40 API CI-4/SL is a high performance diesel engine that is highly recommended for both on and off highway applications. Blended from selected base stocks and additives delivers exceptional protection in the modern high output engines including those with Exhaust Gas Recirculation (EGR) as well as older engines operating on ether low or high sulfur fuels.

FEATURES & BENEFITS

- Minimizes oil consumption
- Neutralizes acids from high sulfur fuel
- Satisfying most diesel engine OEM oil demand
- Exceeds the highest API gasoline engine performance as well
- Particular suitable for the latest diesel engine equipped with EGR

APPLICATIONS

CONTEX SUPREME VOLT SAE 10W40 API CI-4/SL is a universal heavy duty diesel oil meeting the European ACEA standard and American API performance level.

CONTEX SUPREME VOLT SAE 15W40 API CI-4/SL is certified to meet Volvo VDS-3, Mack EO-N, and Renault VI RLD-2 and Cummins CES 20081 specifications.

PERFORMANCE STANDARDS

API CI-4/ SL; ACEA E7-08/ E5-02, ACEA A3/B4-08
MB Approval 228.3; Global DHD-1; Cat ECF-2, ECF-1A; Renault RLD-2
MTU Type II; MAN 3275-1; Volvo VDS 3; Cummins 20076/ 77; Detroit Diesel 93K215; Mack EO-M Plus

TYPICAL CHARACTERISTICS

Particulars	Method	Values
Specific gravity 15 ^o C	ASTM D4052	0.8757
Flash Point ^o C	ASTM D92	200
Pour Point ^o C	ASTM D97	-24
Kinematic Viscosity @ 40 ^o C (cSt)	ASTM D445	108
Kinematic Viscosity @ 100 ^o C (cSt)	ASTM D445	14.5
Viscosity Index	ASTM D2270	142
TBN (mgKOH/g)	ASTM D2896	9.72