



# كونتيننتال الزيوت وزيوت التزييت مروح Continental Oils & Lubricants F.Z.E.

## PRODUCT DATA SHEET

### CONTEX 2T SCOOTER SAE 10W30 API TC JASO FC

---

#### Description

CONTEX 2T SCOOTER SAE10W30 API TC JASO FC is decreasing oil/fuel ratios, increasing power output and the adoption of unleaded petrol has resulted in a requirement for improved lubricant performance for outboard engines. It is formulated with advance performance additive technology and suitable base stock. It is recommended for use in all types of water-cooled outboard engines.

#### Application:

CONTEX 2T SCOOTER SAE10W30 API TC JASO FC is an ash less; self-mixing 2-stroke engine lubricant, this is a mineral lubricant designed for gearboxes with integrated wet clutch. Suitable for all motorcycles, mopeds, scooters and quads (2 stroke or 4 stroke) is recommended for vehicles requiring SAE 10W-30 motor oil or SAE 80 gear oil.

#### Features and benefits

- Exceeds major outboard manufacturer's warranty requirements
- Minimizes piston ring sticking and helps to reduce exhaust port blocking
- Excellent lubricity for use in high-output outboard engines
- Excellent rust and corrosion protection.
- Formulated to provide protection equivalent to many OEM-branded 2-cycle oils.
- Ash less detergent/dispersant formulation helps minimize engine deposits and pre-ignition.
- Protects against piston and cylinder scuffing.
- Reduces spark plug fouling & keeps engine parts clean.

#### Performance Standards

Exceeds major outboard manufacturer's warranty requirements

#### Typical Physical Characteristics

Particulars	Unit	Test Method	Typical Values
Kinematic Viscosity @40 <sup>o</sup> C	cSt	ASTM - D445	75.00
Kinematic Viscosity @100 <sup>o</sup> C	cSt	ASTM - D445	10.90
Viscosity Index	NA	ASTM - D2270	135
Specific Gravity @ 15 <sup>o</sup> C / 60 <sup>o</sup> F	g/cm <sup>3</sup>	ASTM - D4052	0.8650
Flash Point	<sup>o</sup> C	ASTM - D92	134
Pour Point	<sup>o</sup> C	ASTM - D97	-30