

# **PRODUCT DATA SHEET**

## **CONTEX ULTRA MAX SAE 10W30 API SN/CF-4**

# Description

**CONTEX ULTRA MAX SAE 10W30 API SN/CF-4** is made with high proprietary blend of base oil or synthetic base stock and fortified additives to give you maximum protection against sludge deposits and against wear and tear of engines.

### **Applications**

**CONTEX ULTRA MAX SAE 10W30 API SN/CF-4** is recommended for most passenger cars, vehicles SUV's where recommendation from vehicle manual is advised.

#### **Characteristics:**

- Protection for extremely high temperatures
- Protection against harmful deposits and acids which aids in a clean running and lasting engine
- Maybe used at any time in an engines life-cycle and is fully compatible with conventional engine oils.
- It exceeds the requirements of the following industry specifications API SN and all previous categories.

# **Typical Physical Characteristics**

Particulars	ASTM METHOD	VALUES
Density kg/m³	D-4052	869
Flash Point <sup>0</sup> C	D-93	220
Pour Point <sup>0</sup> C	D-97	-36
Viscosity, Cst @ 40 ° C mm²/s	D-445	67.9
Viscosity, Cst @ 100 ° C mm²/s	D-445	10.8
Viscosity Index	D-2270	150
CCS Viscosity @-25 ° C cP	D-5293	6,210

Corporate Address: P.O.Box 40723, Dubai, U.A.E. - Tel.: +971 4 298 1010, Fax: +971 4 294 1167 Factory: P.O. Box 85637, Ras Al Khaimah - U.A.E. - Tel.: +971 7 223 9061, Fax: +971 7 236 5872

E-mail: info@continentaloils.biz - Website: www.continentaloils.com