



كونتيننتال الزيوت وزيوت التزييت مروح

Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

CONTEX ULTRA MAX SAE 10W40 API SN/CF-4

Description

CONTEX ULTRA MAX SAE 10W40 API SN/CF-4 is made with high proprietary blend of base oil or synthetic base stock and fortified additives to give you maximum protection against sludge deposits and against wear and tear of engines.

Applications

CONTEX ULTRA MAX SAE 10W40 API SN/CF-4 is recommended for most passenger cars, vehicles SUV's where recommendation from vehicle manual is advised.

Characteristics:

- Protection for extremely high temperatures
- Protection against harmful deposits and acids which aids in a clean running and lasting engine
- Maybe used at any time in an engines life-cycle and is fully compatible with conventional engine oils.
- It exceeds the requirements of the following industry specifications – API SN and all previous categories.

Typical Physical Characteristics

Particulars	ASTM METHOD	VALUES
Density kg/m ³	D-4052	869
Flash Point ° C	D-93	220
Pour Point ° C	D-97	-33
Viscosity, Cst @ 40 ° C mm ² /s	D-445	104.3
Viscosity, Cst @ 100 ° C mm ² /s	D-445	14.8
Viscosity Index	D-2270	145
CCS Viscosity @-25 ° C cP	D-5293	6,400