



PRODUCT DATA SHEET

CONTEX PRIME ATF DEXRON III

Product Description

CONTEX PRIME ATF DEXRON III is a multi vehicle, fully synthetic fluid designed to meet the demanding requirements of modern passenger vehicles.

CONTEX PRIME ATF DEXRON III can be used in passenger cars, commercial vehicles, construction machinery and boats. The product has a wide range of applications in automatic gearboxes both with and without torque converter, for power steering, in gears or, depending on manufacturer, in hydraulic systems.

CONTEX PRIME ATF DEXRON III is a versatile High Performance ATF. **CONTEX PRIME ATF DEXRON III** is recommended for many passenger car and commercial vehicle automatic transmissions. Additionally, it is suitable for power assisted steering systems and various manual gearboxes for which ATF is specified.

Advantages:

- Outstanding resistance to corrosion, foaming, shearing and rust formation
- High degree of anti-wear and extreme pressure properties
- Outstanding friction and heat transfer properties
- Perfect behaviour at low temperature
- Proven compatibility with elastomers
- Superior oxidation resistance

CONTEX PRIME ATF DEXRON III meets or exceeds the requirements of;

GM DEXRON III, FORD MERCON, ALLISON C-4, CATERPILLAR TO-2

Typical Properties:

Properties	Unit	Method	Values
Colour		Visual	Red
Density at 20 ° C	g/mL	ASTM D4052	0.851
Viscosity at 40 ° C	mm ² /s		34.4
Viscosity at 100 ° C	mm ² /s		7.5
Viscosity Index		ASTM D2983	194
Pour point	° C	ASTM D5950	-45
Flash point	° C		218