



PRODUCT DATA SHEET

CONTEX 2T – TCW3 Marine Oil

Description

Contex 2T- TCW Marine Oil is outboard two cycle engine oil formulated from high performance base stocks and premium quality additives. This is specially designed for 2 strokes gasoline water cooled outboard engines. The ash less additives ensures freedom from spark plug fouling pre-ignitions and deposits. The oil mixes easily with gasoline at all temperatures and in wide ranging proportions.

Benefits:

- Excellent miscibility with the fuel at all temperatures.
- Very good protection against corrosion and wear.
- Optimum protection against deposits and pre-ignition.
- Burns completely without leaving any sticky deposit.
- Keeps piston, rings, plugs and exhaust ports clean.
- Resistance to low temperature gel formation.
- Protection against rust by fresh or salt water.

Application:

- Recommended for use in high output 2 stroke water- or air-cooled gasoline engines
- Suitable for both oil injection and premix systems.
- Suitable for new low emission direct fuel injection two cycle outboard engines.

Performance Standards:

- API TC
- JASO FB
- NMMA TCW3 (R-201111).

Typical Properties:

Particulars	ASTM METHOD	Test Results
Appearance	Visual	B & C
Specific gravity at 15°C, kg/L	D-1298	0.865
Viscosity @ 40 ° C cSt	D-445	25.75
Viscosity @ 100 ° C cSt	D-445	5.0
Brookfield viscosity at -40°C,cP		16600
Flash Point (PMCC) ° C		80
Pour Point ° C	D-97	-36
Sulfated Ash, wt %.		0