



كونتيننتال الزيوت وزيوت التزييت م.م.ح Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

CONTEX 33% COOLANT & ANTIFREEZE

Description

CONTEX 33% COOLANT & ANTIFREEZE is a ready to use coolant antifreeze formulated from mono ethylene glycol and corrosive inhibitors containing no amines, nitrites or phosphates. It provides maximum protection to engine cooling systems of automotive and industrial diesel and gasoline engines.

Benefits:

- Maximizes protection of all metals commonly found in the engine cooling systems
- Keeps engines at optimum operating temperatures contributing to improved fuel economy
- Excellent protection from cavitation, liner pitting, rust, scale and deposits formation
- Compatible with ordinary summer coolants
- Provides year-round cooling properties
- Protects against excessive evaporation
- High boiling point gives better cooling performance in high temperature conditions
- Excellent anti foam properties

Application:

CONTEX 33% COOLANT & ANTIFREEZE is recommended for all cooling circuits in internal combustion engines. It must be replaced every 2 years.

- All types of heavy diesel and gasoline engines, vans, trucks, light vehicles
- Stationary engines regardless of fuel type used
- Marine cooling systems where its required
- Mixed fleets trucks or buses

Performance Level:

- ASTM D 3306
- ASTM D 4985
- SAE J1034
- BS 6580
- BMW
- FORD ESE-M97B44-A



كونتيننتال الزيوت وزيوت التزييت م م ح Continental Oils & Lubricants F.Z.E.

- AS2 2108:2014 TYPE A
- FORD ESE-FM 97B18-C
- JIS K2234
- MAZDA MES MN 121A, 121C-FA04
- NISSAN
- SAAB FSD 8704
- VOLVO
- GENERAL MOTORS

It is the responsibility of the end user to use this product in accordance with Engine Manufacturer recommendations.

Typical Properties:

Particulars	Values
Appearance	Clear
Specific Gravity @ 20° C	1.050
pH, (33% in distilled water)	8.3
Reserve Alkalinity, ml (ph5.5)	5
Boiling Point	130
Glycol Content	33
Freezing Point (33% v/v)	-18