



# كونتيننتال الزيوت وزيوت التزييت مروح Continental Oils & Lubricants F.Z.E.

## PRODUCT DATA SHEET

### CONTEX 2T OUTBOARD SAE10W30 API TC-W3

---

#### Description

**CONTEX 2T OUTBOARD SAE10W30 API TC-W3** A premium lubricant designed to give excellent performance in two-cycle engines used to power outboard motors. It is especially formulated for use in oil injected as well as pre-mixed gasoline/oil lubricated engines.

#### Application:

CONTEX 2T OUTBOARD SAE10W30 API TC-W3 is a self-mixing, fully tested and approved TC-W3™ standard two stroke outboard oil. It is especially formulated for use in oil injected as well as pre-mixed gasoline/oil lubricated engines.

#### Features and Benefits

- Superb anti-wear properties to ensure excellent engine protection
- Prevent corrosion of internal components.
- For use in high performance, water-cooled, 2-stroke engines
- Maintain peak engine performance and reliability.

#### Performance Standards

Meets or exceed Specifications of JASO-FB, NMMA TC-W3, and API-TC

#### Typical Physical Characteristics

Particulars	Unit	Test Method	Typical Values
Kinematic Viscosity @40 <sup>o</sup> C	cSt	ASTM - D445	40.70
Kinematic Viscosity @100 <sup>o</sup> C	cSt	ASTM - D445	7.20
Viscosity Index	NA	ASTM - D2270	135
Specific Gravity @ 15 <sup>o</sup> C / 60 <sup>o</sup> F	g/cm <sup>3</sup>	ASTM - D4052	0.8670
Flash Point	<sup>o</sup> C	ASTM - D92	108
Pour Point	<sup>o</sup> C	ASTM - D97	-45