



PRODUCT DATA SHEET

CONTEX CHAIN OIL

Description

CONTEX CHAIN OIL is specifically designed for the lubrication of chains and guide bars on modern high-speed chain saws operating under severe conditions. It is suitable for use with all types of chain saws equipped with either hand-operated or automatic oilers.

CONTEX CHAIN OIL can also be used in industrial applications where sticky anti-wear oil is preferred. This includes chain drives and plain bearings.

Benefits:

- Tacky nature reduces fling-off from the chain and reduces product wastage, lowering oil consumption while maintaining an adequate oil film in spite of higher centrifugal forces and high local temperatures
- Anti-corrosive properties which limits failure and repair costs
- Provides good wear protection and resistance to foaming
- A red dye is added to allow easy visual determination of chain lubrication while the saw is operating

Application:

- Woodcutters working at moderate temperatures
- Industrial applications for chain lubrication on industrial drives
- All chains, include oil baths, automatic and manual lubricated
- Saw mills, Woodlands , Conveyor systems and mining operations
- Bars and chain

Typical Properties:

Particulars	Method	Values
Colour	Visual	Red
Pour Point ° C	ASTM D97	-15
Flash Point COC ° C	ASTM D492	260
Kinematic Viscosity 40 ° C mm ² /s	ASTM D445	220
Rust Test	ASTM D665	PASS
Viscosity Index	ASTM D2270	130