



كونتيننتال الزيوت وزيوت التزييت مروح

Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

CONTEX COMPRESSOR OIL ISO 32 / ISO 46

Description

Contex Compressor Oils is a high quality industrial lubricant with breakthrough technology, uniquely formulated to help ensure outstanding equipment reliability and efficiency, reducing maintenance cost and downtime for maximum productivity and profitability.

It is formulated with high quality mineral base-oils and a high performance additive system designed to provide exceptional equipment protection and reliability for compressors operating under mild to severe conditions

Contex Compressor Oils were also developed to meet several specifications of different industries and equipment while providing superior protection and performance, wide operating temperature range and suitability for use in the most severe working conditions.

Benefits:

- Outstanding Oxidation and Thermal Stability
- Low Ash and Carbon Formation
- High Load-carrying ability
- Effective Rust and Corrosion Protection

Application:

Contex Compressor Oils are recommended for single and multistage air compressors. It is suitable for reciprocating and rotary type machines with the lower viscosity grades mainly used in rotary compressors. It is also compatible with all metals used in compressor construction and with mineral-oil compatible elastomers used in seals, O-rings and gaskets.

Performance Standards:

DIN 51506 VD-L (1985-09)

Typical Properties:

Particulars	Method	Values	
		ISO 32	ISO 46
Flash Point COC ° C	ASTM D492	230	244
Pour Point ° C	ASTM D97	-39	-36
Kinematic Viscosity 40 ° C mm ² /s	ASTM D445	30.40	43.70
Kinematic Viscosity 100 ° C mm ² /s	ASTM D445	5.70	7.30
Viscosity Index	ASTM D2270	130	130