



كونتيننتال الزيوت وزيوت التزييت مروح Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

CONTEX SUPREME FLUX SAE 10W40 API CI-4

Description

CONTEX SUPREME FLUX SAE 10W40 API CI-4 is a semi synthetic blend, high performance diesel engine oil designed to meet current ACEA requirements and more challenging OEM specifications for Euro IV and V engines. **CONTEX SUPREME FLUX SAE 10W40 API CI-4** provides reliable long oil drain performance and protection.

Benefits:

Reduced maintenance costs - Highly effective detergent additive system minimizes piston crown land deposits which can lead to damaging bore polishing. High base number minimizes corrosive wear in those areas where medium to high sulphur fuel is still encountered.

Maximizes engine life - Proven metallo-organic anti-wear additive system reduces wear in severe service by forming a protective layer on all metal contact surfaces. Wide-range SAE 10W-40 multi-grade viscosity ensures reduced friction at start-up and maximum lubricity at high operating temperatures.

Long oil drain intervals - Exceptional high temperature stability minimizes degradation that leads to sludge formation and oil thickening, and provides extended oil drain capability.

Applications:

CONTEX SUPREME FLUX SAE 10W40 API CI-4 is applicable for naturally aspirated and turbocharged high speed, four-stroke diesel engines, diesel engines meeting Euro V or earlier emission requirements not fitted with Diesel Particulate Filters (DPF), commercial road transport in light, medium and heavy-duty service, Off-highway vehicles

Product Data Sheet

Performance Standards:

- ACEA E4, E7
- API CI-4
- Daimler MB-Approval 228.5
- Deutz DQC-III-10
- Mack EO-N Premium Plus
- MAN M 3277
- MTU Category 3
- Renault RLD-2 / RXD
- Scania LDF-2
- Volvo VDS-3

Corporate Address: P.O.Box 40723, Dubai, U.A.E. - Tel.: +971 4 298 1010, Fax: +971 4 294 1167

Factory: P. O. Box 85637, Ras Al Khaimah - U.A.E. - Tel.: +971 7 223 9061, Fax: +971 7 236 5872

E-mail: info@continentaloils.biz - Website: www.continentaloils.com



كونتيننتال الزيوت وزيوت التزييت م.م.ح Continental Oils & Lubricants F.Z.E.

Typical Properties:

Particulars	Values
Base No. D-2896, mg KOH/g	10
Sulfated Ash, m%	1.0
Pour Point, ° C	-38
Viscosity, mm ² /S @ 40 ° C	104
Viscosity, mm ² /S @ 100 ° C	14.5
Viscosity Index	143
Density @15° C	0.868