كونتيننتال الزيوت وزيوت التزييت م م ح
Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

CONTEX SUPREME NOVA SAE 10W40 API CJ-4 /SM

Description

CONTEX SUPREME NOVA SAE 10W40 API CJ-4 /SM represents the highest level of engine protection and performance ever built into a new lubricant specification. It was designed for all diesel engine applications. It is formulated to provide improved wear protection, deposit and oil consumption control, soot-related viscosity control, prevention of viscosity loss from shearing, used oil low-temperature pumpability and protection from thermal and oxidative breakdown. It also contains a sophisticated additive system that is specifically designed to improve the protection of advanced emission control systems such as diesel particulate filters.

Application:

It is suitable for use in almost all foreign and domestic diesel engines for both the latest emission compliant and older engines.

FEATURES & BENEFITS

- Protects emission control systems
- Outstanding oxidation stability
- Excellent low temperature properties helps speed cold starts
- Universal product for mixed fleet operations
- High 10 TBN

Meets or exceeds Specifications:

API Service Classification CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF/SM, SL, SJ, SH
It has received OEM Approvals for Mack EO-O Premium Plus,
Volvo VDS-4, DDC Power Guard Oil Specification 93K218,
Cummins CES 20081, Renault RLD-3

It is recommended for engines specifying Caterpillar ECF-1a, ECF-2, ECF-3, Mack EO-N Premium Plus 03, Mack EO-N Premium Plus, Mack EO-M PLUS, Mack EO-M, Mercedes Benz p228.31, MAN 3575, MTU Type I and II, Cummins CES 20077 and 20076, Volvo VDS-3, DHD-1, ACEA E9, ACEA E7, and JASO DH-2, Allison C-4

Corporate Address: P.O.Box 40723, Dubai, U.A.E. - Tel.: +971 4 298 1010, Fax: +971 4 294 1167
Factory: P.O. Box 85637, Ras Al Khaimah - U.A.E. - Tel.: +971 7 223 9061, Fax: +971 7 236 5872
E-mail: info@continentaloils.biz - Website: www.continentaloils.com

Typical Physical Characteristics

Particulars	ASTM METHOD	Test Results
Density @ 15^0 C	ASTM D4052	0.892
Viscosity, Kinematic 40 ^{0} C	ASTM D445	120
Viscosity, Kinematic 100 ^{0} C	ASTM D445	15.7
Viscosity Index	ASTM D2270	138
Flash Point ^{0} C	ASTM D92	238 (460)
Pour Point ^{0} C	ASTM D97	-33 (-27)
Total Base Number mg KOH/g	ASTM D2896	10
Sulfated Ash	ASTM D874	1.0

Corporate Address: P.O.Box 40723, Dubai, U.A.E. - Tel.: +971 4 298 1010, Fax: +971 4 294 1167
Factory: P.O. Box 85637, Ras Al Khaimah - U.A.E. - Tel.: +971 7 223 9061, Fax: +971 7 236 5872
E-mail: info@continentaloils.biz - Website: www.continentaloils.com