



# كونتيننتال الزيوت وزيوت التزييت م.م.ح Continental Oils & Lubricants F.Z.E.

## PRODUCT DATA SHEET

### CONTEX SUPREME OVAL SAE 15W40 API CF-4 /SG

---

#### Description

CONTEX SUPREME OVAL SAE 15W40 API CF-4 /SG is a high-quality multigrade engine oils for heavy duty applications in on-highway service.

CONTEX SUPREME OVAL SAE 15W40 API CF-4 /SG are blended with specifically selected high quality mineral and semi-synthetic base stocks together with proven additive technology and viscosity index improver, providing high performance and good durability in service.

#### Application:

Recommended for use in diesel or mixed fleet (diesel gasoline) engine operations on highway service. It is intended for the lubrication of heavy duty diesel engines, naturally aspirated or turbocharged, working under variable conditions and over wide temperature ranges whose manufacturers recommend API CF-4 performance level oils in various types of service including engines used in heavy-duty trucks, construction, mining and farming equipments.

#### FEATURES & BENEFITS

It is formulated with selected technology, to also meet gasoline performance requirements for 1993 and older engines according API SG category. This offers storage simplification and cost effective operation for mixed fleet operators.

#### Typical Physical Characteristics

Particulars	Method	Values
Density, kg/m <sup>3</sup>	ASTM D4052	877.5 at 15° C
Kinematic Viscosity at 100 ° C, mm <sup>2</sup> /s	ASTM D445	14.85
Viscosity Index	ASTM D2270	145
TBN mg KOH/g	ASTM D2896	9.1
Sulphated Ash	ASTM D874	1.3
Flash Point	ASTM D92	234
Pour Point		-34