



# كونتيننتال الزيوت وزيوت التزييت مرمرح Continental Oils & Lubricants F.Z.E.

## PRODUCT DATA SHEET

### CONTEX SUPREME BOLD SAE 15W40 API CD/SF

---

#### Description

**CONTEX SUPREME BOLD SAE 15W40 API CD/SF** engine oil uses exclusive combinations of the latest high-performance additives to ensure that the oil adapts and protects under the full range of pressures and temperatures found in modern engines - from the high temperatures in the pistons, to the extreme loads found in the valve-trains. Featuring extra-active additives to control and sweep away harmful soot and particles found in high performance engines, it delivers excellent soot and viscosity control, outstanding protection against wear and exceptional versatility - one oil for fleets with multiple engines makes.

#### Benefits:

##### Outstanding protection

- Featuring an exclusive additive system to ensure maximum soot handling,
- Heat resistance and high performance due to the use of premium base oil
- Delivers excellent wear protection and long oil life in Euro 3, US 2002 and other advanced engines
- Demonstrated performance for all applications
- **CONTEX SUPREME BOLD SAE 15W40 API CD/SF** has been tested and proven in real-life applications, from severe duty operation in mining and construction operations to heavy duty haulage in some of the world's most severe environments.

##### Improved engine cleanliness

- The exclusive additive system delivers improved engine cleanliness and protection against piston deposits allowing **CONTEX SUPREME BOLD SAE 15W40 API CD/SF** to exceed the demanding requirements of most OEMs.

#### Application:

##### Severe duty heavy duty diesel engines

**CONTEX SUPREME BOLD SAE 15W40 API CD/SF** provides demonstrated protection and performance in the latest high-power heavy-duty diesel engines from Europe, US and Japanese manufacturers in both on-highway and off-highway applications.

##### High technology low emission engines

**CONTEX SUPREME BOLD SAE 15W40 API CD/SF** is designed for use in passenger car, 4wd's and light commercial vehicles and is compatible with dual fuel, diesel and most conventional fuels.



# كونتيننتال الزيوت وزيوت التزييت م م ر ح

## Continental Oils & Lubricants F.Z.E.

### Performance Standards:

Meets and Exceeds API CD/SF

### Typical Properties:

| Particulars                                    | ASTM METHOD | Test Results |
|--|-------------|--------------|
| Kinematic Viscosity 40 ° C mm <sup>2</sup> /s  | D-445       | 105          |
| Kinematic Viscosity 100 ° C mm <sup>2</sup> /s | D-445       | 14.2         |
| Dynamic Viscosity @ -20 ° C mPa s              | D-5293      | 5779         |
| Viscosity Index                                | D-2270      | 137          |
| Total base No. mg KOH/g                        | D-2896      | 8            |
| Density  | D-4052      | 0.875        |
| Flash Point (COC) ° C                          | D-492       | 226          |
| Pour Point ° C                                 | D-97        | -33          |